

PH120 3×4.0mm²

Fire Alarm Cables

NO.7110459



CABLE CONSTRUCTION:

- Conductor:** 4.0mm(sqmm) Plain annealed copper wire, class 1,2 or 5 according to EN60228.
- Insulation:** Fire resistant silicone rubber
BS 6387 CWZ,EN 50200 PH120,IEC 60331
Dia.over Dielectric:3x(0.0150"(3.8 mm))
- Insulation Color:** Brn/Blk/Gry
- Flame Barrier:** Fibre Glass Tape
- Drain Wire:** 0.80 mm Solid tinned copper
- Shield:** Aluminum PET (100% Coverage 20% overlapping)
FR-LSZH (Red or White)
- Jacket:** Dia.over Jacket: 0.405"±0.006"(10.3±0.15mm)
HFFR EN 50290-2,BS7655 LTS1/LTS3,VDE 0207
- Print Legend:** HELLOSIGNAL Fire Alarm Cable PH120 4.0mm² 3 Cores Class N
BC BS 50200:2006 NO.7110459 ××××M/FT



HELLOSIGNAL™


www.zion-communication.com

ELECTRICAL PROPERTIES(at20°C):

- Min.Bend Radius:** 8×Diameter
- Min.Insulation resistance:** 200 MΩ/km
- Max.Working Temperature:** -30°C~+90°C
- Test voitage:** 2000 V
- Max.Operating voitage:** 300 V / 600 V
- Max.resistance of Cond:** Class1,2: 4.55Ω/km Class5: 4.9Ω/km
- Current Carrying Capacity:**
- Nominal Capacitance:**

Cross Section :

Ph120 3×4.0mm²



Test Standards

Flame Tests	Insualtion Integrity	Smoke Density	Corrosive Gas Easurement
BS 4066 part 1 & 3	IEC 60331	BS 7622	BS EN 50267-2-2
EN 50266-2-4	BS 6387 CWZ	IEC/EN 61034	IEC 60754-2
IEC 60332-3-24	EN 50200 PH120	HD 606	BS 6425
IEC/EN 60332-1			

Order Informations :

Package	100M/Wooden Spool,200M/Wooden Spool,500M/Wooden Spool
Delivery time	Normally 25 days after received the deposit.
Brand	HELLOSIGNAL™ OR OEM

Online Service :

Skype	kingtone3
ICQ	246632889
Whatsapp	0086 18268009191
Email	michael@zion-communication.com



www.zion-communication.com
HANGZHOU ZION COMMUNICTON CO.,LTD