

S/FTP CAT 7A Twisted Pair Installation Cable

LAN CABLE

NO. 7112424



Construction

Conductor:	23 AWG Solid Bare Copper
Pairs:	4 Pairs
Insulation:	1.35 mm Skin-Foam-Skin
Insulation Colors:	Blue-White/Blue, Orange-White/Orange Green-White/Green, Brown-White/Brown
Individual Pair shield	Al/PET Foil, Foil face out
Drain Wire	0.40±0.005mm TC
Overall Shield	Tinned copper braid
Rip Cord:	Cotton
Out Jacket:	8.3±0.2 mm PVC CMR




Electrical Characteristics

Impedance	4 - 100MHz	100±15 Ohms
	100 - 200MHz	100±22 Ohms
	200 - 500MHz	100±32 Ohms
Max. Conductor DC Resistance 20°C		8.4 Ohms/100m
Res. unbalance (%)		Max. 2.5
Pair to Ground Capacitance Unbalance		330 pF/100m
Transfer Impedance		Max 10 mOhms/m @100Mhz
Coupling Attenuation		Min 80 dB
Installation temp.		-30 - 50°C
Operation temp.		-20 - 75°C

Cross Section

S/FTP CAT 7A BC PVC CMR



Application

- Suitable for structured premises cabling.
- For transmission of digital and analogue voice and data signals.
- Especially suitable for all Class F applications.
- ISDN, Ethernet 10 Base-T, Fast Ethernet 100 Base-T, Gigabit Ethernet 1000Base-T, 10G Base-T. (IEEE 802.3).
- Token Ring 4/16Mbit/s, TP-PMD/TP/DDI 125Mbit/s, ATM 155Mbit/s. (IEEE 802.5).

Standard

IEC/ISO 61156-5; ISO/IEC 11801

Performance Characteristics

Frequency	RL (Min.)	Insertion Loss (Max.)	Propagation Delay (Max.)	Delay Skew (Max.)	NEXT (Min.)	PSNEXT (Min.)	ELNEXT (Min.)	PSELNEXT (Min.)
MHz	dB	dB/100m	ns/100m	ns/100m	dB	dB	dB/100m	dB/100m
4	23	3.7	552	25	78	75	78	75
16	25	7.3	543	25	78	75	71.2	68.2
20	25	8.2	542	25	78	75	69.3	66.3
25	24.3	9.2	541	25	78	75	67.3	64.3
31.25	23.6	10.3	540	25	78	75	65.4	62.4
62.5	21.5	14.6	539	25	75.5	72.5	59.4	56.4
100	20.1	18.5	538	25	72.4	69.4	55.3	52.3
200	18	26.5	537	25	67.9	64.9	49.3	46.3
250	17.3	29.7	536	25	66.4	63.4	47.3	44.3
300	17.3	32.7	536	25	65.2	62.2	45.8	42.8
400	17.3	38	536	25	63.4	60.4	43.3	40.3
500	17.3	42.8	536	25	61.9	58.9	41.3	38.3
600	17.3	47.1	535	25	60.7	57.7	39.7	36.7

Note: The above transmission performance for the 100M, 20±2°C under the conditions tested.

Order Informations

Marking	HELLOSIGNAL NO.7112424 S/FTP CAT7A 4PR 23AWG PVC CMR XXX (or Per customer's request)
Inner Package	305m/Spool, 305m/Reel (or Per customer's request)
Outer Package	Color Box, Pallet (or Per customer's request)
Delivery time	Normally 25 days after received the deposit.
Brand	HELLOSIGNAL™ OR OEM

Online Service:

Skype	kingtone3
ICQ	246632889
Whatsapp	+86 18268009191
Email	michael@zion-communication.com



www.zion-communication.com
HANGZHOU ZION COMMUNICATION CO.,LTD